

Stainless Steel Uncoated Bands/ Buckle/Tool

Stainless Steel Uncoated Bands

Technical :

- ❖ Material: Stainless Steel Grade 201,304 or 316
- ❖ Working Temp.: -80°C to 538 °C
- ❖ Color: Metallic



Stainless steel bands strapping tool

Model No.: LQA

Feature :

- ❖ Tension and cut off
- ❖ Adjustable tension control
- ❖ Easily remove the excess straps
- ❖ Width: less 25mm



Model No.	Width		Length		Thickness		Packing	
	mm	inch	m	feet	mm	inch	m/box	boxes/ctn
MPS-14	6.4	1/4"	50	164	0.26/0.38	0.010/0.015	50	20
MPS-38	9.5	3/8"	50	164	0.38/0.60	0.015/0.024	50	20
MPS-12	12.7	1/2"	25	82	0.36/0.76	0.014/0.030	25	20
MPS-58	15.9	5/8"	30.5	100	0.36/0.76	0.014/0.030	30.5	20
MPS-34	19	3/4"	30.5	100	0.50/0.76	0.020/0.030	30.5	20

Woolf Teeth Type Buckles

Technical :

- ❖ Material: Stainless Steel Grade 201,304 or 316
- ❖ Working Temp.: -80°C to 538 °C
- ❖ Color: Metallic



Model No.	Width		Thickness
	mm	inch	
BKW-14	6.4	1/4"	0.8/1.2
BKW-38	9.5	3/8"	0.8/1.2
BKW-12	12.7	1/2"	0.8/1.2
BKW-58	15.9	5/8"	0.8/1.2
BKW-34	19	3/4"	0.8/1.5

ASKA COMMUNICATION CORP.
 3034 NW 82ND AVE, DORAL, FL. 33122, U.S.A.
 Phone: 954-708-2387 Email: linda@askacom.com
www.askscom.com

Acetal Weather Resistant Tape/Lock

Acetal Weather Resistant Tape

Technical :

- ❖ Material molding: toughened weather-resistant acetal
- ❖ Temperature Range: -40°C to 85 °C
- ❖ Flammability rating: UL94HB
- ❖ Color: Black
- ❖ Other properties: UV-resistant, halogen free superior resistance to moisture and salt environments.

Product feature:

- ❖ Strap on reel, with separate head
- ❖ Customers can cut the strap at different length in practice
- ❖ Reduce the cost of packing and inventory
- ❖ General packing: 50feet (15m) length



Model No.: AST
Tension/Cut Tool for Acetal Tape

Model No.	Width		Length		Thickness		Min.Tensile Strength	
	mm	inch	m	feet	mm	inch	N	lbs
DT-12*50R	12.7	1/2"	15	50	1.55	0.061	1112	250
DT-34*50R	19	3/4"	15	50	1.55	0.061	1900	425

Note:

- ❖ Other length available
- ❖ The recommended maximum continuous loading for 1/2" straps is 90N per strap
- ❖ For the best results suggested spacing is 35 to 40cm

Acetal Weather Resistant Double Lock

Technical :

- ❖ Material molding: toughened weather-resistant acetal
- ❖ Material locking barb: Marine grade, corrosion-resistant 304 stainless steel
- ❖ Temperature Range: -40°C to 85 °C
- ❖ Flammability rating: UL94HB
- ❖ Color: Black
- ❖ Other properties: UV-resistant, halogen free superior resistance to moisture and salt environments.



Model No.	Width of strap		head height		head width		Packing
	mm	inch	mm	inch	mm	inch	
DTH-12	12.7	1/2"	12.5	0.492	18.8	0.74	25pcs, 100pcs, 1000pcs
DTH-34	10	3/4"	15.1	0.594	27.3	1.075	

ASKA COMMUNICATION CORP.
3034 NW 82ND AVE, DORAL, FL. 33122, U.S.A.
Phone: 954-708-2387 Email: linda@askacom.com
www.askscom.com